



UPC Code : 078477056691

Country Of Origin : Mexico

NEMA :  L6-20R

67W48

Wetguard Watertight Flip Lid Single Locking Receptacle

20 Amp, 250 Volt, NEMA L6-20R, 2P, 3W, Flip Lid with Receptacle, Single Locking Flush Mounting Receptacle, Corrosion Resistant, Grounding, Wetguard Flip Lid, Back & Side Wired, Nickel-Plated Brass Strap, - YELLOW

ROHS Compliant : Yes

- **BATTLE THE ELEMENTS-** Resistant to water, acids, alkalis, and many automotive and industrial lubricants and solvents.
- **ADVANCED LID DESIGN-** Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- **MORE SECURE-** Dual-hasp provides additional lockout /tagout option for added security.
- **DURABLE-** Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP

Electrical Specifications

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Environmental Specifications

Environment : Wet

Flammability : Rated V-0 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Base Material : Nylon

Face Material : Nylon

Grounding Screw : Nickel-
Plated Brass 8-32

Line Contacts : Nickel-Plated
Brass .040 Thick

Terminal Screws : Nickel-
Plated Brass 10-32

Yoke : Nickel-Plated Brass .
050 Thick

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Terminal Accom. : 14-8 AWG

Terminal ID : Brass-Hot,
Green-Ground, White-Neutral

Product Features

Amperage : 20 A

Base Material : Nylon

Brand : Wetguard

Color : Yellow

Device Type : Locking Outlet

Face Material : Nylon

Grounding : Grounding

NEMA : L6-20R

Pole : 2

Standards and Certifications
: UL/CSA

Strap Material : Nickel-Plated
Brass

Termination : Back

Voltage : 250 VAC

Warranty : Limited Lifetime
Warranty

Wire : 3

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406


NEMA : WD-6

NOM : 057

UL Fed Spec WC-596 : File
E13399

UL498 : File E13399

Wiring Diagram



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.